

## Compact Track Loaders / T595 Compact Track Loader

# Specification & Options

■ Standard     Optional    N/A Not Applicable

Units    Metric

### Bobcat T595

Configuration

Standard

Roller Suspension Option

## Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	55.2 kW
Turbocharged Engine	<input checked="" type="checkbox"/>

## Performance

Rated Operating Capacity (SAE)	998 kg
Operating Capacity (50% of Tip)	1425 kg
Tipping Load	2851 kg
Operating Weight	3654 kg
Travel Speed	11.4 km/h
Travel Speed (2-speed option)	16.7 km/h
Ground Pressure (Rubber)	0.35 bar

## Capacities

Fuel Tank	138.2 l
-----------	---------

## Hydraulic System

System Relief @ Quick Couplers	241.32 bar
Auxiliary Std Flow	64.7 l/min
Auxiliary High Flow	101.1 l/min

## Dimension

Length	3378 mm
Length without Attachment	2657 mm
Length with Standard Bucket	3378 mm
Width	1704 mm
Width (with bucket)	1727 mm
Height	1976 mm
Height with Operator Cab	1976 mm
Height to Bucket Hinge Pin	3023 mm
Reach @ Maximum Height	886 mm
Turning Radius	2032 mm
Length of track on ground	1374 mm
Track Width	320 mm
Track Width - Optional	401 mm

## Features

Joystick Control	<input checked="" type="checkbox"/>
Air Conditioning	<input checked="" type="checkbox"/>
Backup Alarm	<input type="checkbox"/>
BICS System (Interlock)	<input type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>
Operating Lights	<input type="checkbox"/>
Suspension Seat	<input type="checkbox"/>
Two Speed Travel	<input checked="" type="checkbox"/>
Deluxe Instrumentation	<input checked="" type="checkbox"/>
Engine Shutdown	<input type="checkbox"/>
Hydraulic Bucket Positioning	<input checked="" type="checkbox"/>
High Flow Option	<input checked="" type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>
Bob-Tach Attachment System	<input type="checkbox"/>
Power Bob-Tach	<input checked="" type="checkbox"/>
ACS (Switchable Controls)	<input checked="" type="checkbox"/>
Ride Control	<input checked="" type="checkbox"/>
Horn	<input type="checkbox"/>